



Neg #: 16Q2971343	City of Rochelle / Wesco Distribution, Inc / City of Rochelle 2500kva
-------------------	--

ITEM	QTY	kVA	EACH (USD)	NL	LL	TL	Conductor	%Z
10	2	2500	36,400.00E	945 @ 85	21297 @ 85	22243	Al/Cu	5.85

ITEM	Shipment
10	10-12 Weeks

Quoted losses are typical for reference purposes only.
Lead times for orders subject to drawing approval will be confirmed upon receipt of approval and release for manufacturing.

Description:

- Type** : Liquid-Filled MTR Padmounted Transformer
- Fluid** : Mineral Oil
- Core** : Amorphous Metal
- Phase** : 3 Phase
- Frequency** : 60 Hz
- Average Winding Rise** : 65 °C
- Ambient Temperature** : 30 °C
- High Voltage** : 13800 Delta
- High Voltage Taps** : +2 -2 2.5%
- High Voltage BIL** : 95kV BIL
- Low Voltage** : 420Y/242
- Low Voltage BIL** : 30kV BIL
- Low Voltage Neutral** : X0 bushing with ground strap
- Feed Configuration** : Loop feed
- Color** : Green (Munsell 7GY 3.29/1.5)

Features (included in price):

TANK & CABINET

- Penta-head cabinet handle bolt

BUSHINGS

- Loadbreak Inserts (dead front) x 6
- ANSI C57.12.26 Fig 2 & 3 HV bushing pattern (minimum)
- 200 amp HV bushing wells x 6
- 10-hole Integral Spade Bushings x 4
- Spade Supports
- ANSI C57.12.26 Fig 3&4a minimum stgrd LV bushing pattern

FUSES

- Bayonet with integral cartridge fuse and isolation link x 3

MONITORING

- Internal Fault Detector (IFD)
- Pressure relief valve
- Therm+ liquid level gauge+ drain valve w/sampler+ prov p/v gaug
- Pressure vacuum gauge

FITTINGS

- Drain valve and sampler



Neg #: 16Q2971343

City of Rochelle / Wesco Distribution, Inc / City of Rochelle
2500kva

MARKINGS

- Special label(s) and/or decal(s)
- Special stencil

OTHER

- 9.5" x 17.5" Tank Handhole Cover
- 24" deep cabinet
- DOE Efficiency (2016)