





CIT Trucks LLC C260  
4301 N Bell School Rd

CITY OF ROCHELLE  
420 N 6TH

Loves Park, Illinois United States 61111  
Phone: (815) 639-2000  
Fax: (815) 637-4097  
Email:

ROCHELLE, Illinois United States  
Phone: (815) 378-5768  
Fax:  
Contact Email:  
Prepared for:

Data	Code	Description	\$ List	Weight
<b>Model</b>				
0000370	O	<b>T370 SERIES CONVENTIONAL</b> Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches; Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floor mat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	88,993	9,642
0070006	O	<b>T370 Class 7: medium-duty Conventional.</b>	0	0
0080050	O	<b>CARB Idle Emissions Reduction Feature for PX-7 and PX-9</b>	100	0
0090022	O	<b>Medium-duty 18k/20k Heavy Front Axle.</b>	0	0
0091230	O	<b>Rock</b>	0	0
0093025	O	<b>Snowplow. Vehicles which are configured for mounting a snowplow to the front. May also have dump or other body. Typically includes some operation off of paved roads. Road usage: majority of Class A &amp; B, do not code for Class D.</b>	0	0
0095010	O	<b>End dump</b>	0	0
0098025	O	<b>U.S. Domestic Registry, 50-State</b>	0	0

**Engine & Equipment**

0129546	O	<b>PACCAR PX-9 350 2017 350@2000 321@2200 1150@1400</b> Includes turbo exhaust brake, no code is used. Diagnostic Plug for data link, Oil Cooler, Aluminum Flywheel Housing. N09200 N205 68...Standard Maximum Speed Limit [LSL] N09220 N207 0...Expiration Distance N09260 P14 68...Maximum Accelerator Pedal Vehicle Speed N09300 P19 68...Maximum Cruise Speed N09360 N203 252...Reserve Speed Function Reset Distance N09380 N202 0...Maximum Cycle Distance N09400 N206 10...Maximum Active Distance N09420 N201 0...Reserve Speed Limit Offset N09440 P11 YES...Engine Protection Shutdown N09460 P06 NO...Gear Down Protection N09480 P26 1400.Max PTO Speed N09500 P02 NO...Cruise Control Auto Resume N09520 P04 NO...Auto Engine Brake in Cruise	12,431	555
---------	---	--	--------	-----

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 12/21/2018 3:11:44 PM  
Effective Date: Jan 1, 2018  
Prepared by: Jeff Heiser

**Complete**

Model Number: T370 SERIES CONVENTIONAL  
Quote/DTPO/CO: Q30826125  
Version Number: 41.20

Data	Code	Description	\$ List	Weight
		N09540 N209 0...Expiration Distance		
		N09560 P520 YES..Enable Idle Shutdown Park Brake Set		
		N09580 P32 5....Timer Setting		
		N09600 P233 YES..Enable Impending Shutdown Warning		
		N09620 P234 60...Timer For Impending Shutdown Warning		
		N09640 P516 35...Engine Load Threshold		
		N09680 P33 NO...Idle Shutdown Manual Overrule		
		N09720 P230 YES..Enable Hot Ambient Automatic Overrule		
		N09740 P46 40...Low Ambient Temperature Threshold		
		N09760 P56 60...Intermediate Ambient Temperature Threshold		
		N09780 P47 80...High Ambient Temperature Threshold		
1000158	O	<b>Prospector Version 43.0</b> Replaces 42.1	0	0
1000684	O	<b>Effective VSL Setting NA</b>	0	0
1000858	O	<b>Engine Idle Shutdown Timer Disabled</b>	0	0
1000859	O	<b>Enable EIST Ambient Temp Overrule</b>	0	0
1000891	O	<b>Eff EIST NA Expiration Miles</b> Use only with MX and Cummins engines	0	0
1002060	S	<b>Air compressor: Cummins 18.7 CFM For Cummins And</b> PACCAR PX engines.	0	0
1031130	S	<b>Air Cleaner: Dry-type firewall mounted w/filter</b> restriction indicator.	0	0
1105230	O	<b>Fan Hub: Horton 2-Speed for ISL9, ISL-G,</b> PX-8 or PX-9	431	0
1121200	S	<b>Cooling module: 1000 square inches</b> T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	0	0
1247194	O	<b>Exhaust:2017 EPA RH Under Cab DPF/SCR For PX-9 w/</b> Single Vertical RH Side of Cab Tailpipe.	2,445	215
1290136	O	<b>Tailpipe: 5 in. single 36 in. 45 degree curved.</b>	33	1
1321145	O	<b>Fuel Filter:Fleetguard FS1003</b> Fuel/Water Separator for PX-9	0	0
1321200	O	<b>Run Aid:None</b> *For Fuel Filter	0	0
1321305	O	<b>Start Aid:12V Heat</b> *For Fuel Filter	62	1
1504006	O	<b>Block heater, PACCAR 1750 watt 120V for PX-6</b> and PX-7, 1000 watt for PX-8 and PX-9 or ISL9 engines .	112	2
1816200	O	<b>Alternator: Bosch 200 amp, brush type</b>	137	0
1821210	O	<b>Batteries: 3 PACCAR GP31 threaded post (700-730)</b> 2100-2190 CCA dual purpose.	177	57
1836100	S	<b>Starter: PACCAR 12 volt electrical system. W/</b> centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/21/2018 3:11:44 PM	<b>Complete</b>	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q30826125
Prepared by:	Jeff Heiser		Version Number:	41.20



Data	Code	Description	\$ List	Weight
1900082	O	<b>Multi-function engine connector for body builder</b> interface for Cummins.	41	0
1901084	O	<b>Body Builder Battery Power Prewire</b>	84	2
<b>Transmission &amp; Clutch</b>				
2011205	O	<b>Transmission: Allison 3000RDS 6-speed</b> w/PTO drive gear. 5th Gen controls. Includes heat exchanger & oil level sensor. Rugged Duty Series for vocational applications. Transynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions. Requires a push button shift control code. Oil temperature gauge is standard on class 8 models.	11,596	291
2406452	O	<b>Driveline: 2 SPL170XL 1 centerbearing</b> requires 3500057 interaxle driveline.	703	70
2409916	O	<b>One bolted centerbearing crossmember.</b> This option upgrades an existing crossmember. The cost does not include the centerbearing and bracket. Crossmember location will be in accordance with Kenworth engineering standards, using the major components specified on the DTPO.	71	11
2410018	O	<b>Torque converter included w/Allison</b> Transmission.	0	0
2410204	O	<b>Delete Allison Fuel Sense</b>	0	0
2429358	O	<b>Rear transmission support springs for</b> transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	74	0
<b>Front Axle &amp; Equipment</b>				
2506181	O	<b>Dana Spicer D2000 Front Axle rated 20K</b> standard track.	4,004	120
2603006	S	<b>Front brakes included w/ front hub package.</b>	0	0
2703211	O	<b>Front Brake:Bendix 16.5x6 air brake package</b> For 18K/20K non-driving front axle. Includes cast drum, 10 bolt iron Preset hub piloted hub, hubcap & slack adjusters.	1,503	113
2866008	O	<b>Front Springs: taperleaf, 20K 2-stage with shocks</b> and 54 in. spring length. T370 with 20K front axle only.	2,116	172
2895305	O	<b>Dual power steering gear: 18/20K</b>	1,965	77
2899336	O	<b>Power Steering Cooler:Radiator Mounted Air-to-Oil</b>	207	11
<b>Rear Axle &amp; Equipment</b>				
3041180	O	<b>Single Dana Spicer S23-172 single reduction axle,</b> single rear axle rated at 23K.	1,058	90
3200538	O	<b>Rear Axle Ratio - 5.38.</b>	0	0
3300000	S	<b>Single rear brakes included w/rear hub package.</b>	0	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/21/2018 3:11:44 PM	<b>Complete</b>	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q30826125
Prepared by:	Jeff Heiser		Version Number:	41.20

Data	Code	Description	\$ List	Weight
3401001	S	<b>23K air brake package includes 16-1/2x7 in.</b> brakes, cast drums, aluminum 10-bolt hub pilot Preset hubs, automatic slack adjusters and oil seals for use w/ 22.5 in. wheels.	0	0
3485009	S	<b>Spring Brake: 3030 high output single.</b>	0	0
3495226	S	<b>Bendix 4S/4M anti-lock brake system.</b>	0	0
3531001	O	<b>Wheel Differential Lock for Dana Spicer Axles</b> S21-170/172, S21-190, S23-170/172, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	924	28
3632277	O	<b>Rear suspension: single Hendrickson HAS230L 23K.</b> Welded steel crossmember & gussets w/shocks at 8.3 in. laden height, 8.5 in. unladen height. Medium-duty. Includes air suspension dump valve. Not rear air disc brake compatible.	1,179	-59
3832313	O	<b>Bolted rear suspension crossmembers for HAS</b> 210/210L or 230/230L. Replaces T3 standard.	187	4
<b>Tires &amp; Wheels</b>				
4038678	O	<b>Front tires: Goodyear G289 WHA 315/80R22.5 20PR.</b> All position. 43.1 in. diameter. 20 in. SLR.	659	78
4238682	O	<b>Rear tires: Goodyear G182 RSD 11R22.5 16PR.</b> 42.1 in. diameter, all position. 19.6 in. SLR. Code is priced per pair of tires.	382	64
4900004	O	<b>Rear Tire Quantity: 4</b>	0	0
5045280	O	<b>Front Wheel: Alcoa 89U64 22.5X9 AL</b> Ultra ONE Wheel.	498	-24
5245162	O	<b>Rear Wheel: Alcoa 88367 22.5x8.25 aluminum with</b> Level One [TM] finish, hub-pilot mount. 7400 lb. maximum rating. Air disc brake compatible. Code is priced per pair of wheels.	762	-88
5859010	O	<b>Single Front Axle: 2 wheels Dura-Bright Buffed.</b> Dura-Bright outboard surface of aluminum wheels.	245	0
5859011	O	<b>Single Rear Axle Wheels: 2 wheels Dura-Bright</b> Buffed. Dura-Bright outboard surface of outer dual or single aluminum wheels.	362	0
5900004	O	<b>Rear Wheel/Rim Quantity: 4</b>	0	0
<b>Frame &amp; Equipment</b>				
6056200	O	<b>Frame Rails: 10-3/4 x 3-1/2 x 3/8in. Steel to</b> 284 in. Truck frame weight is 3.48 lb.-in. per pair of rails. Section modulus is 17.80, RBM is 2,132,000 in.-lbs per rail. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.	389	232
6309912	O	<b>Delete bumper: For use with heavy duty front</b> frame brackets for customer installed winch bumper. Requires a bumper setting code.	0	-24
6319409	S	<b>40.9 in. Bumper setting. Requires a bumper code.</b>	0	0
6390078	O	<b>Heavy duty front frame brackets provide structure</b> for customer installed winch bumper	1,335	101

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 12/21/2018 3:11:44 PM **Complete** Model Number: T370 SERIES CONVENTIONAL  
 Effective Date: Jan 1, 2018 Quote/DTPO/CO: Q30826125  
 Prepared by: Jeff Heiser Version Number: 41.20



Data	Code	Description	\$ List	Weight
6390103	S	Front mudflaps.	0	0
6391201	O	Custom Frame Layout: one chassis	1,380	0
6400634	O	Battery box cantilever aluminum BOC with smooth aluminum cover.	101	2
6409902	O	Battery box location: RH Side.	91	15
6451059	O	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under. End plates will be painted standard black frame color.	0	0
6490124	O	Five-piece bolted crossmember assembly with 16mm frame fasteners, center and rear frame.	166	-32
6490427	O	Aluminum underbell crossmember. Only with non-drive front axle 16K and greater. For T370 only.	84	19
6490430	O	Bolted Rear Cab Support Crossmember. Replaces T3 standard.	132	17
6679911	O	Component Restriction: Do Not Drive- Unit may be decked.	0	0
6742009	S	Square end-of-frame w/o crossmember; non-towing.	0	0
<b>Fuel Tanks &amp; Equip</b>				
7010075	O	Fuel Tank: 75 US gallon 22in. aluminum under replace. Class 8 fuel tank includes an anti-siphon device on the filler neck.	119	-11
7722011	O	Small round DEF tank. 11 gallons of usable volume. The DEF tank will be located on the side you specified. If you have specific configuration or body builder concerns, please utilize the Custom Frame Layout option. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	150	0
7840015	O	Polish only one aluminum tank.	246	0
7840038	O	Polished cover for 1 DEF tank any size.	278	3
7889061	O	Polished stainless steel tank straps for 1 tank.	61	0
7889203	O	Standard DEF to fuel fill ratio: 2:1 or greater.	0	0
7889604	O	DEF tank location is on the LH.	0	0
7920075	O	Location: 75 gal fuel tank LH under cab	0	0
<b>Cab &amp; Equipment</b>				
8024310	S	<b>Cab: Curved Glass Conventional.</b> Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	0	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 12/21/2018 3:11:44 PM **Complete** Model Number: T370 SERIES CONVENTIONAL  
Effective Date: Jan 1, 2018 Quote/DTPO/CO: Q30826125  
Prepared by: Jeff Heiser Version Number: 41.20



Data	Code	Description	\$ List	Weight
8080137	O	<b>Cab door bearing blocks, top &amp; bottom.</b>	30	0
8090310	S	<b>Hood: Sloped aerodynamic hood includes grill &amp; separate bumper.</b>	0	0
8108010	S	<b>Cab heater: W/integral defrosters &amp; A/C 45,000</b> btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	0	0
8201200	O	<b>Adjustable telescoping tilt steering column.</b>	568	10
8203060	O	<b>5 sets of keys. Replaces standard 2 sets of keys.</b>	28	0
8205087	O	<b>Auto Suspension Dump W/PTO Engagement Interlock.</b> This feature automatically dumps air from the truck suspension when any PTO is engaged. Required with air suspensions used on dump trucks, trailer dumps, or with no tilt fifth wheels. This allows the suspension to deflate while hoist is up and helps alleviate any imbalance that can occur with air bags inflated. Required with roll back flat bed or roll on/off with air suspensions. This allows the suspension to deflate while body is up and helps alleviate tipping and imbalance that can occur with air bags inflated. Auto air suspension dump with PTO engagement is not for use without a PTO. PTO controls must be installed by the factory.	45	2
8205118	O	<b>Information for customer-installed PTO Chelsea</b> 277. 10-bolt. Available only with Allison 3000/4000 series transmissions.	44	0
8205123	O	<b>Switch &amp; Wiring for Customer-Installed PTO.</b> Electric over hydraulic PTO. Includes switch guard. Wiring is routed to LH frame for connection to the customer installed PTO. No air controls are provided with this code.	220	0
8208496	O	<b>Three spare switches: Wired to power.</b>	113	0
8220106	O	<b>Gauge: Dash mounted air filter restriction gauge.</b>	119	0
8221144	O	<b>Gauge: Air suspension pressure gauge.</b>	80	0
8222712	O	<b>Gauge: Fuel filter restriction gauge.</b>	143	0
8240014	U	<b>Additional Speedo Sensor Wire In Cab</b>	245	0
8282009	S	<b>Instrument package: Includes speedometer,</b> tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	0	0
8330003	S	<b>Cab interior: Pinnacle. Includes vinyl headliner</b> & cab back panel, slate gray interior, dark slate gray seats, floor mats, LH/RH inside sunvisor & door courtesy lights.	0	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 12/21/2018 3:11:44 PM **Complete** Model Number: T370 SERIES CONVENTIONAL  
 Effective Date: Jan 1, 2018 Quote/DTPO/CO: Q30826125  
 Prepared by: Jeff Heiser Version Number: 41.20

Data	Code	Description	\$ List	Weight
8410491	O	<b>Driver seat: Kenworth Air cushion Plus HB Mordura</b> Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6-23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	134	2
8480490	O	<b>Rider seat: Kenworth Toolbox Plus HB Mordura.</b> Standard features include fixed base and backrest, tool box seat base w/ door, and dual armrests. Seat cushion is 19.5 inches. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	146	2
8601421	O	<b>Kenworth Radio with AM/FM/WB/USB and Bluetooth</b>	358	4
8699916	O	<b>Dash mounted CB assembly: W/leads &amp; antennas.</b> Includes dual antenna leads & dual antennas.	198	4
8700083	O	<b>Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet &amp; a storage compartment.</b>	86	0
8700144	O	<b>Dome lamp over driver door.</b>	24	0
8700154	O	<b>Self cancelling turn signal: W/head light dimmer switch .</b>	22	0
8800733	O	<b>Grabhandle: LH w/ short extension over door.</b>	37	4
8800734	O	<b>Grabhandle: RH w/ short extension over door.</b>	37	4
8832115	O	<b>Daylite Door: LH/RH includes RH peeper window</b>	0	0
8841618	O	<b>Dual rectangular air horn 23 in. LH &amp; RH top of roof. Includes air horn covers.</b>	253	11
8850300	S	<b>Look-Down, Pass. Door, Stainless 8.5x4.4</b>	0	0
8850717	O	<b>Mirror: RH Fender Mounted, Round Convex</b>	101	4
8865000	O	<b>Mirror: Dual Kenworth aerodynamic heated motorized 7 in. x 13 in. mirrors. Mirror shell painted cab color, mirror arms black. LH/RH convex mirrors 5 in. x 7 in. heated. Mirror brackets set for 8-1/2 ft load width. Switch located on door pad.</b>	441	26
8879213	O	<b>Electric-powered LH &amp; RH door window lifts.</b> Switch located on door.	127	0
8879911	O	<b>Two corner &amp; one rear cab stationary windows</b> 17.5 in. x 16 in. (two) & 17 in. x 36 in. (one).	559	24
8890135	O	<b>Exterior stainless steel sunvisor.</b>	393	11

#### Lights & Instruments

9010801	S	<b>Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam</b>	0	0
9022137	O	<b>Marker Lights: Five, rectangular, LED</b>	99	0
9030010	S	<b>Turn Signal Lights: Mounted on fender</b>	0	0

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/21/2018 3:11:44 PM	<b>Complete</b>	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q30826125
Prepared by:	Jeff Heiser		Version Number:	41.20



Data	Code	Description	\$ List	Weight
9058037	O	<b>Switch &amp; Wiring for Customer-Installed Floodlight</b> W/O Electrical Pass-Through - 1st Set. Wire Coiled BOC/BOS.	106	0
9070138	S	<b>Combination Stop, Tail, Turn &amp; Backup Lights RH &amp; LH.</b>	0	0
9080202	O	<b>Switch &amp; Wiring: Customer-installed dual beacon</b> lights w/o insulators. Coiled wire behind dash.	89	1
9090151	O	<b>Wiring:Cust. Install Trlr Elec. Brake Controller.</b> Class 8/T4 Content Includes Dash Signals: Ignition Power (20A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To EOF Junction Box. These Signals Are Located Near The NavPlus HD Area. No Need To Code For An Additional End of Frame Junction Box. EOF Junction Box Signals Are: Ground, Tail Lamp, Marker Lamp, Left Turn, Right Turn, Stop Lamp and Electric Trailer Brake Controller Wired To Dash. Medium Duty (not T4) Content Includes A MP 280 Series Connector In Dash Near Driver Door Connections With Signals: Battery Power (40A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To Chassis Connector. Medium Duty (not T4) 2 Way Deutsch Chassis Connector Located Near Back of Cab, With Signals: Ground and Electric Trailer Brake Controller Wired To Dash Connector.	133	1
9090312	O	<b>Body Builder Lighting Harness Coiled End Of Frame</b> For Additional Customer Installed Exterior Lighting. Harness Includes Circuits for Additional Customer Installed Tail Lamps, Turn Lamps, Stop Lamps, and Marker Lamps.	80	0
9090845	O	<b>Circuit Breakers: Replacing fuses. Does not</b> apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	37	0
<b>Air Equipment</b>				
9101215	S	<b>Air Dryer Bendix AD-IS heated Puraguard</b>	0	0
9140328	O	<b>Trailer ABS electric supply through SAE J560</b> 7-pin connector per TMC RP137).	0	0
<b>Extended Warranty</b>				
9200008	O	<b>Base Warranty - PACCAR PX-9 Engine</b> 24 months / 250,000 miles / 402,336 km / 6250 hours.	0	0
9200022	S	<b>Base Warranty - Standard Service Medium Duty</b> 12 months / Unlimited miles & km	0	0
<b>Miscellaneous</b>				
9400072	O	<b>Ship to Dealer.</b>	0	0
9409852	O	<b>GHG Secondary Manufacturer: Does Not Apply</b>	0	0
9490206	O	<b>Warning triangle reflector kit: Shipped loose.</b> Kit consists of 3 triangles in plastic carrying case. Not floor mounted.	43	4
9490404	O	<b>One 5 lb. dry chemical type fire extinguisher</b> mounted outboard of driver seat. Class ABC.	122	11

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 12/21/2018 3:11:44 PM **Complete** Model Number: T370 SERIES CONVENTIONAL  
Effective Date: Jan 1, 2018 Quote/DTPO/CO: Q30826125  
Prepared by: Jeff Heiser Version Number: 41.20



Data	Code	Description	\$ List	Weight
9490645	O	<b>Zinc Phosphate frame rail paint processing.</b> Requires frame rail code. Code is for 1 pair of rails.	310	0
<b>Paint</b>				
9700000	O	<b>Paint color number(s).</b> N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK	0	0
9943050	O	<b>Day Cab Standard Paint</b>	0	0
9944820	O	<b>1 - Color Paint - Day Cab</b> Color will be White if no other color is specified.	0	0
9965510	S	<b>Base coat/clear coat.</b> The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0	0

Total Adjusted Price (W/O Freight & Warranty & Surcharges)	\$143,643
Freight Charge	\$2,325
Options Not Subject to Discount	\$0
Surcharges Not subject to Discount	\$0
Total Weight	11880 lb

**Prices and Specifications Subject to Change Without Notice.**

Unpublished options may require review/approval.  
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	12/21/2018 3:11:44 PM	<b>Complete</b>	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jan 1, 2018		Quote/DTPO/CO:	Q30826125
Prepared by:	Jeff Heiser		Version Number:	41.20



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



Bill To: 0009562  
 CIT TRUCKS, LLC  
 4301N BELL SCHOOL RD  
 LOVES PARK, IL 61111

*Wing mit*

Ship To: 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com; jheiser@cittrucks.co  
 Phone: Fax:

Confirm To: OZZY Comment:

Customer P.O.	Ship VIA	F.O.B.	Terms Net 10 Days	Quote Expiration 1/6/2019
---------------	----------	--------	----------------------	------------------------------

Ordered	Unit	Item Number	Each Price	Extended Price
---------	------	-------------	------------	----------------

1.00	EACH	TRUCK PACKAGE APPLICATION: NEW KENWORTH T-370 SINGLE AXLE CAB AND CHASSIS WITH 96" CAB TO AXLE MEASUREMENT, FRONT FRAME EXTENSIONS, AUTOMATIC TRANSMISSION WITH PTO PROVISIONS, FACTORY PLOW LIGHT PLUG, FACTORY "GROUND SPEED CONNECTION POINT	83,005.00	83,005.00
------	------	--	-----------	-----------

THIS PACKAGE TO INCLUDE:

- 1- DURACCLASS 10' SL-316 201-2B STAINLESS STEEL DUMP BODY
- 1- CROSS MEMBERLESS
- 1- DURACCLASS 1821 DOUBLE ACTING UNDERBODY HOIST
- 1- 3/16" STAINLESS STEEL LONGSILLS
- 1- 18" CAB SHIELD
- 1- 1/4" AR400 FLOOR
- 1- 34" 10 GA. FRONT
- 1- 24" 10 GA. SIDES
- 1- 34" 10 GA. SIX PANEL TAILGATE
- 1- AIR TAILGATE
- 1- 5/8 ROD WALK RAIL
- 1- COUGAR DC-3200 VIBRATOR
- 1- 10" OAK SIDE BOARDS--PAINTED BLACK
- 1- GREASEABLE LINKAGE AND HINGE POINTS
- 1- BONNELL FOLDING LADDER DRIVER SIDE OF BODY
- 1- FRONT FLAPS WITH "T" BRACES
- 1- REAR FLAPS
- 1- UNDERBODY PAINTED BLACK
- 1- UPPERBODY LEFT UNPAINTED
- 1- 12" STAINLESS SPILL PAN--UNPAINTED

MISC:

- 1- CUSTOMER WANTS 12" OVERHANG ON DUMP TO CLEAR ASPHALT PAVER
- 1- NOX-RUST FRAME AND UNDERBODY
- 1- ONE PAIR "EVERBLADE" HEATED WIPER BLADES

CENTRAL HYDRAULIC SYSTEM:

- 1- OMBF HOT SHIFT PTO
- 1- TXV92 "LOAD SENSE" HYDRAULIC PUMP
- 1- ADD-A-STACK HYDRAULIC VALVE WITH AIR ACTUATORS TO OPERATE HOIST, PLOW, WING, AUGER / SPINNER
- 1- HP3000 SERIES HIGH PRESSURE FILTER



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



**Bill To:** 0009562  
 CIT TRUCKS, LLC  
 4301N BELL SCHOOL RD  
 LOVES PARK, IL 61111

**Ship To:** 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com; jheiser@cittrucks.co

Phone:  
 Fax:

Confirm To: OZZY

Comment:

Customer P.O.	Ship VIA	F.O.B.	Terms Net 10 Days	Quote Expiration 1/6/2019
---------------	----------	--------	----------------------	------------------------------

Ordered	Unit	Item Number	Each Price	Extended Price
---------	------	-------------	------------	----------------

- 1- 5100EX ELECTRIC SPREADER CONTROLLER--CLOSED LOOP
- 1- BONNELL 30 GA. STAINLESS STEEL HYDRAULIC TANK WITH RETURN FILTER
- 1- BONNELL STAINLESS STEEL HYD. VALVE ENCLOSURE
- 1- BONNELL LOW OIL / HIGH TEMP AUTO SHUT DOWN SYSTEM
- 1- ALL REQUIRED PLUMBING

CONSOLE SYSTEM:

- 1- BONNELL CUSTOM CONSOLE
- 1- APSCO AIR CONTROLS
- 1- HOIST--WITH INTERLOCK
- 1- PLOW LIFT
- 1- PLOW ANGLE
- 1- WING TOE
- 1- WING HEEL
- 1- BONNELL VCMS-SS184 WARNING SWITCH PANEL
- 1- "FORCE" 5100EX SPREADER CONTROLLER

ELECTRICAL SYSTEM:

- 1- BONNELL IGNITION ACTIVATED BATTERY DISCONNECT RELAY SYSTEM
- 1- MINI FUSE CIRCUIT PROTECTION PANEL
- 1- BONNELL VCMS-SS184 ELEVEN SWITCHES / WARNING PANEL
- 1- BONNELL WIRE HARNESSSES

LIGHTING SYSTEM

- 1- ONE PAIR ABL-3830-0575 PLOW LIGHTS ON STAINLESS HOOD BRACKETS
- 1- ONE PAIR ABL-5001-0016 LED WORK LIGHTS MOUNTED NEXT TO THE PLOW LIGHTS
- 1- TWO PAIR ECCO-3920A AMBER FLASHERS ON CAB SHIELD FACING FRONT
- 1- ONE ECCO-ED3777AW FLASHER ON EACH SIDE OF CAB SHIELD
- 1- ONE PAIR ECCO-3965AC AMBER / WHITE FLASHERS ON CAB SHIELD FACING REAR
- 1- ONE PAIR PM-M820R-10 STT LIGHTS ON CAB SHIELD FACING REAR
- 1- ONE ECCO-3965AC AMBER / WHITE FLASHER IN EACH REAR POST
- 1- ONE PM-M820R-10 STT LIGHT IN EACH REAR POST
- 1- ONE PM-M192R MARKER LIGHT ON SIDE OF EACH REAR POST
- 1- ONE M20343R ICC THREE LIGHT BAR ON REAR HINGE
- 1- ONE PAIR PM-M817R-9 4" ROUND STT LIGHTS RECESSED IN REAR HITCH
- 1- ONE PM-M820C-10 BACK UP LIGHT RECESSED IN REAR HITCH
- 1- ONE NAP-12250304 LICENSE PLATE LIGHT ON REAR HITCH
- 1- ONE VEL-697112 BACK UP ALARM
- 1- ONE "RV" TRAILER PLUG
- 1- ONE ABL-2000-0018 LED SPINER LIGHT--MOUNTED UNDER DRIVER SIDE



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



**Bill To:** 0009562  
 CIT TRUCKS, LLC  
 4301N BELL SCHOOL RD  
 LOVES PARK, IL 61111

**Ship To:** 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com; jheiser@cittrucks.co

Phone:  
 Fax:

Confirm To: OZZY

Comment:

Customer P.O.	Ship VIA	F.O.B.	Terms	Quote Expiration
			Net 10 Days	1/6/2019

Ordered	Unit	Item Number	Each Price	Extended Price
		CORNERPOST 1- ONE ABL-2000-0018 LED WING LIGHT		
		REAR HITCH  1- BONNELL PLATE REAR HITCH 1- DRILL HOLES ONLY FOR A PH 20 PINTLE 1- ONE PAIR STT LIGHTS 1- ONE BACK UP LIGHT 1- ONE RV TRAILER PLUG 1- ONE PAIR D-RINGS		
1.00	EACH	CAB SHIELD CAB SHIELD - CUSTOM FABRICATED FOR SPECIFIED TRUCK AND BODY. CONFIGURED AS FOLLOWS:  *MATERIAL IS TO BE 201 STAINLESS STEEL. *PAN WIDTH- 18". *WIDTH- DETERMINED. *HEIGHT TO BE DETERMINED TO BOTTOM OF PAN. *4 FRONT FACING EVENLY SPACED OBLONG LIGHT HOLES. *4 REAR FACING OBLONG LIGHT HOLES. *1 SIDE FACING OBLONG LIGHT HOLE IN EACH SIDE FACING OUT.		
1.00	EACH	PLOW HITCH HITCH FOR SNOW PLOW PLOW HITCH FOR A KENWORTH T370 WITH FRAME EXT. HITCH INSTALLED ON NEW TRUCK PACKAGE TYPE OF MOUNT - HEAVY FRONT FRAME -SIDE PLATES TYPE OF HITCH FRAME - QX HITCH (SIDE-BY-SIDE) BASE MODEL: HFF-QX RIGID PLOW LIFT ARM		
1.00	EACH	*H10400  1/2" Side Plates. (Included in Standard Price of Side Plate Hitch)		
1.00	EACH	*H10170  4" X 10" Double Acting Cylinder W/Nitrided Rod		



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



**Bill To:** 0009562  
 CIT TRUCKS, LLC  
 4301 N BELL SCHOOL RD  
 LOVES PARK, IL 61111

**Ship To:** 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com; jheiser@cittrucks.co  
 Phone: Fax:

**Confirm To:** OZZY **Comment:**

Customer P.O.	Ship VIA	F.O.B.	Terms	Quote Expiration
			Net 10 Days	1/6/2019

Ordered	Unit	Item Number	Each Price	Extended Price
1.00	EACH	*H10310  Stainless Hood Mounted Light Brackets. (Side of Hood)		
1.00	EACH	*H10420  Cross Over Relief Valve Kit (Installed or Not Installed)		
1.00	EACH	PLOW  11ST49TT7Q PRICE COMPLETE WITH OPTIONS 11' LONG STRAIGHT STEEL SNOW PLOW HEIGHT IS 49" TORSION (TT)(ONE PIECE TORSION TRIP) METRO REVERSING ASSEMBLY PAINTED ORANGE POLYURETHANE ENAMEL		
1.00	EACH	*NO RG NO RUNNING GEAR REQUIRED		
1.00	EACH	*P10130  Level Raise Lift System with Lift Chains for High Country Plows (MX1 & MC1)		
1.00	EACH	*P10210  Quick attach loop (plow section installed)		
1.00	EACH	*P10425  3/8" x 12" Rubber flap kit installed		
1.00	EACH	*P10465  Plow stand - installed ( to hold hook up point @ desired height when detached )		
1.00	EACH	*P10470		



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



Bill To: 0009562  
 CIT TRUCKS, LLC  
 4301N BELL SCHOOL RD  
 LOVES PARK, IL 61111

Ship To: 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com; jheiser@cittrucks.co

Phone:  
 Fax:

Confirm To: OZZY

Comment:

Customer P.O.	Ship VIA	F.O.B.	Terms	Quote Expiration
			Net 10 Days	1/6/2019


Ordered	Unit	Item Number	Each Price	Extended Price
		36" Blaze orange markers		
1.00	EACH	*P10500		
		5/8" x 6" C1084 Steel cutting edge		
1.00	EACH	*P10555		
		1/2" Quick Couplers installed (one set/per plow) pioneer PHD-4000-4		
1.00	EACH	<b>WING</b> BONNELL WING PLOW PRICE COMPLETE WITH OPTIONS MID MOUNT JR WING TOE CYLINDER STROKE IS 12" (8" MAX BENCHING) (STD) BUFFER BRACE SUPPORT IS LOCATED IN FRONT OF TIRES CUTTING EDGE LENGTH: 7'-0 TRIP MECHANISM: NON-TRIP MOLDBOARD CUTTING EDGE TYPE: HIGH CARBON STEEL CUTTING EDGE SIZE: 3/4X6 STANDAR EDGES 6'-9' NO DISCHARGE END CURB SHOE PLOW MARKER: 24" YELLOW JUMBO LOCK VALVE: YES- DOES GET LOC VALVE MOLDBOARD COLOR: ORANGE		
1.00	EACH	*W10160		
		Wing lock valve - installed to cylinder		
1.00	EACH	*W10190		
		24" Jumbo blade guide on dischrage end with bolt on bracket		
1.00	EACH	*W10500		
		Standard 3/4" x 6" C1084 Steel Cutting Edge		



1385 Franklin Grove Rd  
 Dixon, IL 61021  
 815-284-3819 \* 815-284-8815 Fax  
 800-851-9664  
 www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
 Quote Date: 12/7/2018



**Bill To:** 0009562  
 CIT TRUCKS, LLC  
 4301N BELL SCHOOL RD  
 LOVES PARK, IL 61111

**Ship To:** 4155  
 CITY OF ROCHELLE  
 420 N 6TH ST  
 ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com;jheiser@cittrucks.co  
 Comment:

Confirm To: OZZY

Customer P.O.	Ship VIA	F.O.B.	Terms	Quote Expiration
			Net 10 Days	1/6/2019

Ordered	Unit	Item Number	Each Price	Extended Price
---------	------	-------------	------------	----------------

1.00 EACH PREWET SYSTEM

BONNELL CONFIGURED PREWET SYSTEM  
 TYPE: BEHIND THE CAB SYSTEM  
 CLOSED LOOP SYSTEM  
 HYDRAULIC LIQUID PUMP  
 SEE BELOW FOR DETAILS

1.00 EACH \*BC-120P-1-200

Behind the Cab Prewet System with one 120 Gallon Poly Tank, Stainless Steel Tank Brackets, and 2" Plumbing.

1.00 EACH \*L10120

Hydraulic Prewet Pump in a Stainless Enclosure to Operate a Closed Loop System. Includes an IP68 Wire Connection for Feedback Signal.

1.00 EACH \*L10315

2" Male Quick Fill Kit Installed.

1.00 EACH \*L10355

Flush Kit. (Includes small poly flush tank) Installed.

1.00 EACH UT SPREADER

MODEL U696-DD-S2-24L-1 UNDER TAILGATE SPREADER  
 \* 6" AUGER DIAMETER, 4" PITCH  
 \* DIRECT DRIVE WITH A 22.8 CUBIC INCH MOTOR  
 \* FABRICATED OF 201 STAINLESS STEEL MATERIAL  
 \* SPREADER SHALL HAVE ONE DROP PORT  
 \* DROP PORT(S) IS 24" OFFSET FROM LEFT SIDE  
 \* AUGER SHALL HAVE REVERSE FLIGHTING  
 \* ONE SPINNER ASSEMBLY  
 \* SPINNER(S) ARE POWERED BY 2.8 CUBIC INCH MOTOR(S)  
 \* 18" POLYURETHANE SPINNER DISC  
 \* INCLUDES MOUNTING HARDWARE



1385 Franklin Grove Rd  
Dixon, IL 61021  
815-284-3819 \* 815-284-8815 Fax  
800-851-9664  
www.bonnell.com \* info@bonnell.com

# Quote

Quote Number: 0129329  
Quote Date: 12/7/2018



Bill To: 0009562  
CIT TRUCKS, LLC  
4301N BELL SCHOOL RD  
LOVES PARK, IL 61111

Ship To: 4155  
CITY OF ROCHELLE  
420 N 6TH ST  
ROCHELLE, IL 61068

Phone: (815) 639-2000 Fax: (815) 639-0100 kreed@cittrucks.com;jheiser@cittrucks.co  
Phone: Fax:

Confirm To: OZZY

Comment:

Customer P.O.	Ship VIA	F.O.B.	Terms Net 10 Days	Quote Expiration 1/6/2019
---------------	----------	--------	----------------------	------------------------------

Ordered	Unit	Item Number	Each Price	Extended Price
		* INCLUDES A 72" SPRAY BAR KIT INSTALLED		
		* MITERED CORNER LONG STAINLESS TAILGATE SHIELDS		

15% RESTOCKING FEE ON RETURNED ITEMS  
NO RETURN ON SPECIAL ORDER ITEMS OR ELECTRICAL ITEMS

SUBMITTED BY: \_\_\_\_\_

0006 Scott Blumeyer TG

NOTE: ALL TAXES WILL BE EXTRA IF APPLICABLE.  
NOTE: PRICES ARE IN EFFECT FOR 30 DAYS ONLY. IF A PRICE INCREASE OCCURS - IT WILL BE ADDED.

NOTE: BIDS MAY REQUIRE A 20% DEPOSIT UPON PURCHASE  
NOTE: INSTALL DATE IS BASED ON CHASSIS ARRIVAL DATE.

ACCEPTED BY: \_\_\_\_\_

\*\*BILL TO: \_\_\_\_\_

PO Number: \_\_\_\_\_

DATE ACCEPTED: \_\_\_\_\_

CHASSIS ARRIVAL DATE: \_\_\_\_\_

Net Order:	83,005.00
Less Discount:	0.00
Freight:	0.00
Sales Tax:	0.00
<b>Quote Total:</b>	<b>83,005.00</b>

VIN# \_\_\_\_\_

MAKE: \_\_\_\_\_

MODEL: \_\_\_\_\_

W.B. \_\_\_\_\_ C.A.: \_\_\_\_\_

TRANS MODEL: \_\_\_\_\_

ENGINE: \_\_\_\_\_

PAINT CODE: \_\_\_\_\_

\*\*CHANGES MAY CAUSE DELAYS AND FEES.



## PURCHASE ORDER

Rockford - 4301 North Bell School Road Loves Park, IL 61111 - 815.639.2000

Dealership

CITY OF ROCHELLE

12-20-18

New

Used

Purchaser's Name

Date

Stock #	VIN	Year	Make	Model	Retail	FET	Total
		2020	KW	T370	\$ 94,466.00		\$ 94,466.00
	WING UNIT				\$ 83,005.00		\$ 83,005.00

Additional Option: PAYMENT IS DUE ON OR BEFORE TRUCK IS DELIVERED BONNELL

Additional Option: SOURCE WELL

Additional Option:

Additional Option:

Total \$ 177,471.00

Tax Exempt / ICC # :

Sales Tax: %

\$ 150.00  
DOC Charges

License

\$ 95.00  
Title

\$ 8.00  
Registration

Prep Charge

\$ 253.00

\*Total Cash Delivered Price \$ 177,724.00

S E T T L E M E N T	Pending Approval <input type="checkbox"/> Non-Refundable			Cash Deposit Submitted with Order	
	Description of Trade			Allowance for Trade-In as Appraised	
	Year	NONE	Make	Model	Less Pay Off Amount
	VIN		Type		Net Equity
	Additional Information:			Total Credits	
				Unpaid Cash Balance due on Delivery	\$ 177,724.00

THIS AGREEMENT, entered into this \_\_\_\_\_ day of \_\_\_\_\_ by and between \_\_\_\_\_ NONE and CIT Trucks, Inc. witnesseth that agrees that the above vehicle being considered for trade-in by CIT Trucks, Inc. will be:

- (1) Dispatch ready according to D.O.T. requirements  
Exceptions: \_\_\_\_\_
- (2) All components, i.e. engine, transmission, rear axles(s), electrical, air conditioning, and attaching components are in good working mechanical condition.  
Exceptions: \_\_\_\_\_
- (3) Physical Condition: No structural damage, broken glass, or damage to interior (normal wear and tear is expected and excluded).  
Exceptions: \_\_\_\_\_
- (4) All factory installed emission control devices on the engine, or truck, including the DPF system and the DEF system must be operating and fully functional. The engine / truck must be able to demonstrate a successful "regeneration" of the DPF system filter. As well as pass a visual and cleaning inspection by a CIT Trucks, Inc. tech.
- (5) Front brakes 3/8" minimum shoe depth, rear 1/2". Brake drums will meet D.O.T. requirements.  
Exceptions: \_\_\_\_\_

Purchaser's Signature

420 N 6TH ST

Street Address

ROCHELLE IL

City & State

61068

Zip

815-561-2078

Business Phone

Residential Phone

JEFF HEISER

Salesman Name

**This order is not valid unless signed and accepted by dealer or authorized representative.**

Dealer or Authorized Representative

\*Quote good for 30 days only

This Purchase Order is not a commitment on the part of CIT Trucks, LLC to deliver or make ready the vehicle(s) at a particular point in time. Delivery of the vehicle(s) is subject to the formal approval and production scheduling by the vehicle's manufacturer. Purchaser understands that CIT Trucks, LLC shall not be liable for failure to deliver or delay in delivering the vehicle(s) covered by this order.

Purchaser's Initials